



Codice articolo Item code Produktcode	Portata alla coppia kg Loading capacity per pair kg Bekämpfungsfähigkeit pro Paar kg			Lunghezza mm Length mm Länge mm	Larghezza int. mm Internal width mm Innenbreite mm	Larghezza est. mm External width mm Aussenbreite mm	Altezza bordo mm Height of raised edge mm Randhöhe mm	Altezza montante mm Height of ramps' profile mm Trägerhöhe mm	Peso alla coppia kg Weight for pair kg Gewicht pro Paar kg
	Passo-Wheelbase Achsenabstand								
	750 mm	1000 mm	1250 mm		A	B	C	D	
M070/15	2500	2750	3000	1500	240	300	23	70	19
M070/20	1525	1906	2500	2000	240	300	23	70	24
M070/25	1090	1270	1525	2500	240	300	23	70	28
M070/30	850	960	1085	3000	240	300	23	70	34
M070/35	700	765	845	3500	240	300	23	70	39
M070/40	597	647	706	4000	240	300	23	70	43

Larghezza minima impronta ruota/cingolo 150 mm. Minimum width of tracks/wheels 150 mm. Mindestbreite der Reifen / Ketten mm 150.

M070/15L	2450	2450	2450	1500	440	500	23	70	26
M070/20L	1525	1906	2450	2000	440	500	23	70	32
M070/25L	1090	1270	1525	2500	440	500	23	70	38
M070/30L	850	960	1085	3000	440	500	23	70	46
M070/35L	700	765	845	3500	440	500	23	70	52
M070/40L	597	647	706	4000	440	500	23	70	58

Larghezza minima impronta ruota/cingolo 300 mm. Minimum width of tracks/wheels 300 mm. Mindestbreite der Reifen / Ketten mm 300.

	1000 mm	1250 mm	1500 mm						
M075/20	3200	3500	3500	2000	240	300	19	75	32
M075/25	2150	2600	3200	2500	240	300	19	75	39
M075/30	1600	1850	2150	3000	240	300	19	75	43
M075/35	1300	1450	1600	3500	240	300	19	75	49
M075/40	1100	1150	1300	4000	240	300	19	75	54
M075/45	900	1000	1050	4500	240	300	19	75	62

Larghezza minima impronta ruota/cingolo 150 mm. Minimum width of tracks/wheels 150 mm. Mindestbreite der Reifen / Ketten mm 150.

	1000 mm	1250 mm	1500 mm						
M080/20	2510	3000	3000	2000	240	300	23	80	26
M080/25	1674	2009	2510	2500	240	300	23	80	31
M080/30	1255	1435	1674	3000	240	300	23	80	38
M080/35	1004	1116	1255	3500	240	300	23	80	43
M080/40	837	913	1004	4000	240	300	23	80	48
M080/45	717	772	837	4500	240	300	23	80	55

Larghezza minima impronta ruota/cingolo 150 mm. Minimum width of tracks/wheels 150 mm. Mindestbreite der Reifen / Ketten mm 150.

Gamma disponibile CON o SENZA BORDO.
Range available both WITH or WITHOUT EDGES.
Rampenserie MIT oder OHNE RAND verfügbar.