



Codice articolo Item code Produktcode	Portata alla coppia kg Loading capacity per pair kg Belastungsfähigkeit pro Paar kg			Lunghezza mm Length mm Länge mm	Larghezza int. mm internal width mm Innenbreite mm	Larghezza est. mm External width mm Ausßenbreite mm	Altezza bordo mm Height of raised edge mm Randhöhe mm	Altezza montante mm Height of ramps' profile mm Trägerhöhe mm	Peso alla coppia kg Weight for pair kg Gewicht pro Paar kg
	Passo-Wheelbase Achsenabstand								
	1000 mm	1250 mm	1500 mm		A	B	C	D	
M115A/25	3000	3600	4000	2500	300	360	36	115	42
M115A/30	2250	2570	3000	3000	300	360	36	115	45
M115A/35	1800	2000	2250	3500	300	360	36	115	51
M115A/40	1500	1635	1800	4000	300	360	36	115	57
M115A/45	1285	1385	1500	4500	300	360	36	115	65
M115A/50	1125	1200	1285	5000	300	360	36	115	70

Larghezza minima impronta ruota/cingolo 200 mm. Minimum width of tracks/wheels 200 mm. Mindestbreite der Reifen / Ketten mm 200.

M115A/25L	3000	3600	4000	2500	340	400	36	115	45
M115A/30L	2250	2570	3000	3000	340	400	36	115	54
M115A/35L	1800	2000	2250	3500	340	400	36	115	62
M115A/40L	1500	1635	1800	4000	340	400	36	115	69
M115A/45L	1285	1385	1500	4500	340	400	36	115	78
M115A/50L	1125	1200	1285	5000	340	400	36	115	86

Larghezza minima impronta ruota/cingolo 300 mm. Minimum width of tracks/wheels 300 mm. Mindestbreite der Reifen / Ketten mm 300.

M125/25	4500	4500	4500	2500	300	360	36	125	47
M125/30	3435	3925	4500	3000	300	360	36	125	58
M125/35	2750	3050	3435	3500	300	360	36	125	66
M125/40	2290	2500	2750	4000	300	360	36	125	73
M125/45	1965	2115	2290	4500	300	360	36	125	84
M125/50	1720	1830	1965	5000	300	360	36	125	92

Larghezza minima impronta ruota/cingolo 200 mm. Minimum width of tracks/wheels 200 mm. Mindestbreite der Reifen / Ketten mm 200.

M125/25L	4500	4500	4500	2500	340	400	36	125	50
M125/30L	3435	3925	4500	3000	340	400	36	125	61
M125/35L	2750	3050	3435	3500	340	400	36	125	69
M125/40L	2290	2500	2750	4000	340	400	36	125	78
M125/45L	1965	2115	2290	4500	340	400	36	125	89
M125/50L	1720	1830	1965	5000	340	400	36	125	97

Larghezza minima impronta ruota/cingolo 300 mm. Minimum width of tracks/wheels 300 mm. Mindestbreite der Reifen / Ketten mm 300.

Gamma disponibile CON o SENZA BORDO.
Range available both WITH or WITHOUT EDGES.
Rampenserie MIT oder OHNE RAND verfügbar.