



Codice articolo Item code Produktcode	Portata alla coppia kg Loading capacity per pair kg Belastungsfähigkeit pro Paar kg	Lunghezza mm Length mm Länge mm	Larghezza int. mm Internal width mm Innenbreite mm	Larghezza est. mm External width mm Aussenbreite mm	Altezza bordo mm Height of raised edge mm Randhöhe mm	Altezza montante mm Height of ramps' profile mm Tragerhöhe mm	Peso alla coppia kg Weight for pair kg Gewicht pro Paar kg
---	---	---------------------------------------	--	---	---	---	--

Passo-Wheelbase
Achsenabstand

	1250 mm	1500 mm	1750 mm	A	B	C	D		
M165/25	6385	6385	6385	2500	420	480	43	165	74
M165/30	6385	6385	6385	3000	420	480	43	165	91
M165/35	5620	6325	6385	3500	420	480	43	165	103
M165/40	4600	5060	5620	4000	420	480	43	165	114
M165/45	3890	4215	4600	4500	420	480	43	165	130
M165/50	3375	3615	3890	5000	420	480	43	165	142

Larghezza minima impronta ruota/cingolo 350 mm. Minimum width of tracks/wheels 350 mm. Mindestbreite der Reifen / Ketten mm 350.

M165/25L	6385	6385	6385	2500	450	510	43	165	76
M165/30L	6385	6385	6385	3000	450	510	43	165	93
M165/35L	5620	6325	6385	3500	450	510	43	165	105
M165/40L	4600	5060	5620	4000	450	510	43	165	118
M165/45L	3890	4215	4600	4500	450	510	43	165	135
M165/50L	3375	3615	3890	5000	450	510	43	165	147

Larghezza minima impronta ruota/cingolo 400 mm. Minimum width of tracks/wheels 400 mm. Mindestbreite der Reifen / Ketten mm 400.

Gamma disponibile CON o SENZA BORDO.

Range available both WITH or WITHOUT EDGES.

Rampenserie MIT oder OHNE RAND verfügbar.