



Codice articolo Item code Produktcode	Portata alla coppia kg Loading capacity per pair kg Belastungsfähigkeit pro Paar kg			Lunghezza mm Length mm Länge mm	Larghezza int. mm internal width mm Innenbreite mm	Larghezza est. mm External width mm Aussenbreite mm	Altezza bordo mm Height of raised edge mm Randhöhe mm	Altezza montante mm Height of ramps' profile mm Tragerhöhe mm	Peso alla coppia kg Weight for pair kg Gewicht pro Paar kg
	Passo-Wheelbase Achsenabstand			A	B	C	D		
	1500 mm	1750 mm	2000 mm						
M200/25	12000	12000	12000	2500	500	600	57	200	112
M200/30	12000	12000	12000	3000	500	600	57	200	137
M200/35	10625	12000	12000	3500	500	600	57	200	156
M200/40	8500	9445	10625	4000	500	600	57	200	174
M200/45	7085	7730	8500	4500	500	600	57	200	198
M200/50	6070	6540	7085	5000	500	600	57	200	206
M200/55	5310	5665	6070	5500	500	600	57	200	223

Larghezza minima impronta ruota/cingolo 450 mm. Minimum width of tracks/wheels 450 mm. Mindestbreite der Reifen / Ketten mm 450.

Codice articolo Item code Produktcode	Portata alla coppia kg Loading capacity per pair kg Belastungsfähigkeit pro Paar kg			Lunghezza mm Length mm Länge mm	Larghezza int. mm internal width mm Innenbreite mm	Larghezza est. mm External width mm Aussenbreite mm	Altezza bordo mm Height of raised edge mm Randhöhe mm	Altezza montante mm Height of ramps' profile mm Tragerhöhe mm	Peso alla coppia kg Weight for pair kg Gewicht pro Paar kg
	Passo-Wheelbase Achsenabstand			A	B	C	D		
	1500 mm	1750 mm	2000 mm						
M230/25	14000	14000	14000	2500	500	600	71	230	123
M230/30	14000	14000	14000	3000	500	600	71	230	150
M230/35	14000	14000	14000	3500	500	600	71	230	171
M230/40	12000	13340	14000	4000	500	600	71	230	191
M230/45	10008	10918	12000	4500	500	600	71	230	219
M230/50	8578	9238	10008	5000	500	600	71	230	239
M230/55	7506	8006	8578	5500	500	600	71	230	260

Larghezza minima impronta ruota/cingolo 450 mm. Minimum width of tracks/wheels 450 mm. Mindestbreite der Reifen / Ketten mm 450.

Gamma disponibile CON o SENZA BORDO.

Range available both WITH or WITHOUT EDGES.

Rampenserie MIT oder OHNE RAND verfügbar.